



## KBT200OD low headroom hoist-trolley

### Product information



Hand-operated trolley in combination with the Rema® Select 200OD hand chain hoist.  
Only available in combination with the Rema® Select 200 OD manual chain hoist.

#### Properties

- Extremely low building height (135-235 mm).
- Suitable for beams with both straight and sloping flange.
- Maintenance-free ball bearings.
- Wheel rupture supports for extra safety.
- Hand chain operated trolley.
- Technical specifications for manual hoist see Rema® Select 200 OD chain hoist.

#### Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operation.

#### Option

- Available in other lifting and operating heights.

**Marking:** CE-marked

| Part Code | WLL<br>ton | Model        | Flange width<br>mm | Load Chain dia x pitch<br>mm | Hand Chain Ø x pitch<br>mm | Chain falls | Min. curve radius<br>mm | A<br>mm | B1<br>mm | B2<br>mm | C1<br>mm | C2<br>mm | D1<br>mm | D2<br>mm | E1<br>mm | E2<br>mm | F<br>mm | H<br>mm | L<br>mm | M1<br>mm | M2<br>mm | Weight<br>kg |
|-----------|------------|--------------|--------------------|------------------------------|----------------------------|-------------|-------------------------|---------|----------|----------|----------|----------|----------|----------|----------|----------|---------|---------|---------|----------|----------|--------------|
| 0923001   | 1          | KBT200OD-1   | 74-150             | 5.0 X 15                     | 5.0 X 23.7                 | 2           | 2.500                   | 554     | 206      | 234      | 129      | 151      | 117      | 223      | 217      | 134      | 27,5    | 135     | 348     | 40       | 18       | 69           |
| 0923003   | 2          | KBT200OD-2   | 82-156             | 6.3 X 19.1                   | 5.0 X 23.7                 | 2           | 4.000                   | 684     | 254      | 406      | 149      | 211      | 165      | 265      | 240      | 152      | 36,5    | 160     | 392     | 50       | 24       | 118          |
| 0923005   | 3,2        | KBT200OD-3.2 | 103-223            | 8.0 X 24.2                   | 5.0 X 23.7                 | 2           | 4.500                   | 765     | 279      | 461      | 169      | 236      | 165      | 325      | 240      | 173      | 44      | 190     | 499     | 55       | 28       | 181          |
| 0923007   | 5          | KBT200OD-5   | 119-215            | 8.0 X 24.2                   | 5.0 X 23.7                 | 4           | 6.000                   | 873     | 336      | 524      | 201      | 279      | 184      | 327      | 259      | 180      | 39      | 235     | 512     | 65       | 37       | 293          |
| 0923009   | 6,3        | KBT200OD-6.3 | 119-215            | 8.0 X 24.2                   | 5.0 X 23.7                 | 4           | 6.000                   | 873     | 336      | 524      | 201      | 279      | 184      | 327      | 259      | 180      | 39      | 235     | 512     | 65       | 37       | 296          |

Blueprint

