



## C-15E DIN-580 Eye bolt type

### Product information



The safe working load is only suitable for hoisting and pulling in line.  
The lifting eye must not be loaded sideways.

**Marking:** According to standard, CE-marked

**Standard:** DIN 580

| Part Code | GTIN No.      | WLL<br>ton | Thread<br>mm | Model                  | D2<br>mm | D3<br>mm | D4<br>mm | E<br>mm | H<br>mm | L<br>mm | M<br>mm | Weight<br>kg |
|-----------|---------------|------------|--------------|------------------------|----------|----------|----------|---------|---------|---------|---------|--------------|
| 3015101   | 8717365183522 | 0,14       | M8           | DIN580-C15E-M8-140KG   | 20       | 36       | 20       | 6       | 36      | 13      | 8       | 0,06         |
| 3015103   | 8717365183539 | 0,23       | M10          | DIN580-C15E-M10-230KG  | 25       | 45       | 25       | 8       | 45      | 17      | 10      | 0,11         |
| 3015105   | 8717365183546 | 0,34       | M12          | DIN580-C15E-M12-340KG  | 30       | 54       | 30       | 10      | 53      | 20,5    | 12      | 0,18         |
| 3015107   | 8717365183553 | 0,49       | M14          | DIN580-C15E-M14-490KG  | 35       | 63       | 35       | 12      | 60      | 27      | 14      | 0,28         |
| 3015109   | 8717365183560 | 0,7        | M16          | DIN580-C15E-M16-700KG  | 35       | 63       | 35       | 12      | 62      | 27      | 16      | 0,28         |
| 3015111   | 8717365183577 | 1,2        | M20          | DIN580-C15E-M20-1200KG | 40       | 72       | 40       | 14      | 71      | 30      | 20      | 0,43         |
| 3015113   | 8717365183584 | 1,8        | M24          | DIN580-C15E-M24-1800KG | 50       | 90       | 50       | 18      | 90      | 36      | 24      | 0,84         |
| 3015115   | 8717365183591 | 2,5        | M27          | DIN580-C15E-M27-2500KG | 50       | 90       | 50       | 18      | 90      | 36      | 27      | 1,22         |
| 3015117   | 8717365183607 | 3,2        | M30          | DIN580-C15E-M30-3200KG | 65       | 108      | 60       | 22      | 109     | 45      | 30      | 1,66         |
| 3015119   | 8717365183614 | 4,6        | M36          | DIN580-C15E-M36-4600KG | 75       | 196      | 70       | 26      | 128     | 54      | 36      | 2,65         |

## Blueprint

