



Hoist traverse beam REMA, with 2 adjustable hooks.

Product information



Properties

- Surface finish: zinc phosphate primer RAL 2004 (orange).
- Capacity range labelling.
- Black-and-yellow safety markings at beam ends.
- Hooks equipped with safety latches.
- High quality steel hooks grade 10.

Option

- Sandblasting and painting in every RAL color.
- Higher load capacity and bigger dimensions on request.

Marking: According to standard, CE-marked

Standard: EN 1677-1, EN 12100, EN 13155

Part Code	GTIN No.	WLL ton	Model	B2 mm	C mm	D mm	H mm	L mm	n x k mm	Weight kg
3962041	8717365017841	1	TRA-VE-1000-1M	140	85	55	380	1.000	2 x 150	30
3962043	8717365017858	1	TRA-VE-1000-1,6M	140	85	55	400	1.600	3 x 150	40
3962045	8717365017865	1	TRA-VE-1000-2,5M	160	85	55	420	2.500	5 x 150	67
3962047	8717365017872	1	TRA-VE-1000-3,15M	170	85	55	420	3.150	7 x 150	100
3962049	8717365017889	1,6	TRA-VE-1600-1,6M	150	85	55	480	1.600	2 x 200	48
3962051	8717365017896	1,6	TRA-VE-1600-2,5M	170	85	55	500	2.500	4 x 200	83
3962053	8717365017902	1,6	TRA-VE-1600-3,15M	190	85	55	520	3.150	5 x 200	120
3962055	8717365017919	1,6	TRA-VE-1600-4M	200	85	55	520	4.000	7 x 200	171
3962057	8717365017926	2,5	TRA-VE-2500-2,5M	180	85	70	540	2.500	4 x 200	115
3962059	8717365017933	2,5	TRA-VE-2500-3,15M	200	85	70	560	3.150	5 x 200	140
3962061	8717365017940	2,5	TRA-VE-2500-4M	220	85	70	580	4.000	7 x 200	202
3962063	8717365017957	2,5	TRA-VE-2500-5M	240	85	70	600	5.000	8 x 200	284

Blueprint

