



HS stationary lifting tables

Product information



The universal stationary lifting table for lifting heavy loads can be used in a space-saving manner by placing the lifting table in a pit.

Properties

- Robust support construction.
- Profile reinforced table.
- Solid steel scissors.
- This lifting table is equipped with an aluminium safety frame.
- Support inspection for safe maintenance.
- Overload protection.
- Hose rupture safety valve.
- Hard chromed cylinder and piston rod.
- Lifetime lubricated bearings.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

Standard delivery

- Includes 24 V push button switch with emergency stop.
- Removable lifting eyes for easy transport.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 1570

Part Code	GTIN No.	WLL ton	Model	Lifting times	Motor power kW	Lifting cycle/hour	A mm	B mm	C mm	D mm	E mm	H mm	Weight kg
3459005	8717365021534	0,5	HS05-01	25	1,1	21	243	2.000	800	680	1.615	1.043	193
3459001	8717365016257	1	HS1-01	20	0,75	21	248	1.300	820	640	1.240	1.033	160
3459007	8717365021824	1	HS1-04	30	1,1	15	283	1.700	1.000	640	1.580	1.343	210
3459002	8717365016264	2	HS2-01	20	1,5	21	273	1.300	850	785	1.220	1.043	235
3459003	8717365021817	2	HS2-06	35	2,2	15	293	2.000	1.000	785	1.600	1.343	375
3459004	8717365016271	4	HS4-01	40	2,2	13	288	1.700	1.200	900	1.600	1.098	375
3459006	8717365021541	4	HS4-06	45	2,2	10	348	2.200	1.200	900	2.000	1.448	505

Blueprint

