



TL Gear winch

Product information



Properties

- Load pressure brake.
- Adjustable crank length; backwind-free.
- The drums and the shaft supported by needle bearings.
- Paint finish and enamel varnish are standard.
- Capacity min. 2%

Standard delivery:

- Does not include wire rope.

Option:

- Wire rope on request with hook and safety latch.

Marking: According to standard, CE-marked

Standard: EN 13157, EN 12100

Part Code	GTIN No.	WLL ton	Model	Cable Diameter mm	Lift/crank turn (mm)	Max. reel capacity mm	Force on the handle (kg)	Load capacity last layer kg	load capacity 1st layer kg	A	B	C	D	G	H	J	K	L	M	N	O	P	S	Weight kg
2015008	8717365273742	0,15	TL-0.150	4	122	13	11	68	150	65	168	128	40	6	40,5	35	9 (3x)	102	-	89	303	280	128,5	4
2015009	8717365008733	0,3	TL-0.3	5	21	25	7	120	300	200	300	268	168	20	55	70	12 (4x)	145	198	108	318	280	128,5	10
2015012	8717365273759	0,6	TL-0.6	6	28	12	10	323	600	200	300	268	168	20	55	60	12 (4x)	145	203	110	318	325	128,5	11
2015013	8717365008757	1	TL-1.0	10	21	28	15	684	1.000	250	250	212	170	6,7	113	102	16.5 (4x)	212	266	118	483,5	350	132,2	28
2015014	8717365273766	1,5	TL-1.5	14	14	21	12	844	1.500	-	-	-	-	-	-	-	-	-	-	-	-	-	-	27,5

Blueprint

