REMA® Work made easy.
HOISTING & LIFTING



WW worm gear winches

Product information

REMA®

Properties

- Load pressure brake.
- Adjustable crank length; backwind-free.
- Drums and axes run on needle bearings.
- Models above load capacity of 2 kg have two speeds, which is operated by changing the crank over.
- Paint finish and enamel varnish are standard.

Standard delivery

- Does not include wire rope.

Option

- Steel wire rope on request.

Marking: According to standard, CE-marked
Standard: EN 13157, EN 12100

Part Code	GTIN No.	WLL ton	Model	Cable Diameter mm	Lift/crank turn (mm)	Max. reel capacity mm	Force on the handle (kg)	Load capacity last layer kg	load capacity 1st layer kg	Weight kg
2016001	8717365008771	0,25	WW-250	4	17	104	3,5	95	250	13
2016003	8717365008788	0,5	WW-500	6	20	78	9	239	500	16
2016005	8717365008795	1	WW-1000	8	13	63	15,5	542	1.000	26
2016007	8717365008801	1,5	WW-1500	10	9	41	19	845	1.500	28
2016009	8717365008818	2	WW-2000	12	12/6	46	22/13	1.129	2.000	60
2016011	8717365008825	3	WW-3000	14	11/6	52	27/14	1.861	3.000	78
2016012	8717365024269	4	WW-4000	16	11/4	52	35/13	2.390	4.000	80
2016013	8717365008849	5	WW-5000	18	12/4	40	58/17	3.165	5.000	115

Blueprint

