



REMA steel jacks	208
Rema-All	208
VHS Steel jack	209
Sluice-winding jacks	210

REMA[®]
HOLLAND

DMK
5000
CM805261
2009/05 CE

DMK steel lifting jacks



Properties

- Low forces thanks to the optimum transmission ratios.
- Robust construction with large-size, stable foot plate.
- Safety crank with foldable handle.
- Type **DMK** standard model.
- Type **DMKR** with ratchet crank.

Norm:

- EN12100-1/2, EN13157, DIN-EN7355

Type	S.W.L. (kg)	Construction height (mm)	Lifting height (mm)	Height of claw in lowest position (mm)	Weight (kg)	ProductId
DMK-1.5	1500	725	350	70	12	1950015
DMK-3.0	3000	725	350	75	20	1950030
DMK-5.0	5000	725	300	75	29	1950050
DMK-10.0	10000	800	300	85	42	1950100
DMKR-1.5	1500	725	350	70	15	1950016
DMKR-3	3000	725	350	75	23	1950031
DMKR-5	5000	725	300	70	27	1950051

Rema-All



ACCORDING ASME / ANSI SAFETY STANDARD.

Properties

- A patented overload limiter excludes misoperation, the "safety link" hinders continuing lifting while the jack takes hold of load.
- Long life due to cast parts and easy operation.
- Extra large foot plate for stability.
-

IMPORTANT:

- Lifting height 300 mm, load capacity 3000 kg.
- Lifting height 600 mm, load capacity 2250 kg.
- Lifting height 900 mm, load capacity 1600 kg.
- Lifting height 1000 mm, load capacity 1000 kg.

Norm:

- EN12100-1/2, DIN-EN7355
- ASME / ANSI SAFETY STANDARD

Type	S.W.L. (kg)	Construction height (mm)	Maximum height (mm)	Weight (kg)	ProductId
REMA-ALL	3000	1215	1200	14	0310050

VHS and KBH Steel jacks



Properties

- Safety crank with foldable handle.
- Type **VHS** standard model
- Type **VHS-R** with Ratchet crank
- Type **KBH** short model
- Type **KBH-R** short model with ratchet crank.

Norm:

- EN12100-1/2, EN13157, DIN-EN7355

Type	S.W.L. (kg)	Construction height (mm)	Hefhoogte (mm)	Klauwhoogte laagste stand (mm)	Weight (kg)	Productid
VHS-1.5	1500	725	350	70	12	1901031
VHS-3.0	3000	725	350	75	20	1901033
VHS-5.0	5000	725	300	70	25	1901035
VHS-10.0	10.000	800	300	90	40	1901040
VHS-R-1.5	1500	725	350	70	12	1901131
VHS-R-3.0	3000	725	350	75	20	1901133
VHS-R-5.0	5000	725	300	70	25	1901135
VHS-R-10.0	10.000	800	300	90	40	1901140
KBH-1.5	1500	570	300	70	11	1902031
KBH-3.0	3000	570	300	75	18	1902033
KBH-5.0	5000	600	300	70	22	1902035
KBH-10.0	10.000	650	300	80	38	1902040
KBH-R-1.5	1500	570	300	70	11	1902131
KBH-R-3.0	3000	570	300	75	18	1902133
KBH-R-5.0	5000	600	300	70	22	1902135
KBH-R-10.0	10.000	650	300	80	38	1902140

Options: Special steel jacks on request



Adjustable



Ratchet



Cable drum
steel jack



Rail jack



Tree trunk
steel jack



Rack and pinion
jack

311 and 312 sluice-winding jacks



Properties

- Series 311 is supplied with rear plate.
- Series 312 is supplied with foot plate.
- Safety crank with foldable handle.

Option

- Other stroke and pinon-gear rack lengths can be manufactured based on your requirements.

Norm:

- EN12100-1/2, EN13157, DIN-EN7355

Type	S.W.L. (kg)	Construction height (mm)	Lifting height (mm)	Hole size heart on heart (mm)	Weight (kg)	ProductId
311-1.5	1500	1150	800	130x160	14	2218001
311-3.0	3000	1260	800	165x220	24	2218003
311-5.0	5000	1280	800	180x250	32	2218005
312-1.5	1500	1150	800	130x 70	14	2219001
312-3.0	3000	1260	800	130X 80	24	2219003
312-5.0	5000	1280	800	200x100	32	2219005