

| | |
|-------------------------------|-----|
| Pallet trucks | 222 |
| Special version pallet trucks | 224 |
| High lifters | 225 |



PT pallet truck



The new REMA PT pallet trucks fitted with pump (model 25) are very manoeuvrable and user-friendly. The tandem fork rollers are advantageous when using these pallet truck on a less smooth floor. Single truck roller designs are frequently used in the transport sector (rubber steer wheels and polyurethane rollers).

Properties

- Quick-Lift pump (model 25) for a quick lifting of pallets.
- The pump unit has an overload protection function.
- A chromate-coated and polished piston rod provides a long life for the hydraulic cylinder.

Operation:

- All pump functions can be operated precisely by means of the three-position control lever.
- Variable lowering speed even under load.
- The tow bar will automatically return to vertical position.

Fork:

- The robust plate steel fork profiles have flattened ends and they are fitted with in- and outrunning rollers to move pallets easier.

Technical specifications:

- Highest fork position: 200 mm.
- Steering wheel: 200 mm.
- Fork rolls: 82 mm.

Option

- Foot parking brake (3410000).

Norm:

- EN12100-1/2, EN 3691-5



Foot parking brake (3410000)



| Type | S.W.L. (kg) | Model | Dimensions (mm) | min height (mm) | width of fork (mm) | Material steering wheels | Model fork roller | Material fork rollers | Weight (kg) | ProductId |
|-------------|----------------|-------------|--------------------|--------------------|-----------------------|-----------------------------|----------------------|--------------------------|----------------|-----------|
| PTS-25TPP | 2500 | Standard | 1150 x 540 | 85 | 160 | Polyurethane | Tandem | Polyurethane | 75 | 3410001 |
| PTK-25SPR-E | 2500 | Short | 1000 x 540 | 85 | 160 | Rubber | Single | Polyurethane | 86 | 3410005 |
| PTC-25SPR | 2500 | Extra short | 800 x 540 | 85 | 160 | Rubber | Single | Polyurethane | 75 | 3410017 |
| PTK-25TPR | 2500 | Short | 1000 x 540 | 85 | 160 | Rubber | Tandem | Polyurethane | 75 | 3410015 |
| PTS-25TPR | 2500 | Standard | 1150 x 540 | 85 | 160 | Rubber | Tandem | Polyurethane | 75 | 3410013 |
| PTSKB-25TPP | 2500 | Short/wide | 1000 x 680 | 85 | 160 | Polyurethane | Tandem | Polyurethane | 75 | 3410014 |
| PTS-25TNN | 2500 | Standard | 1150 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 75 | 3410011 |
| PTB-25TNN | 2500 | Standard | 1150 x 685 | 85 | 160 | Nylon | Tandem | Nylon | 80 | 3410012 |
| PTL-18TNN | 1800 | Long | 1500 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 80 | 3410021 |
| PTM-12TNN | 1200 | Medium long | 1800 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 80 | 3410025 |
| PTX-10TNN | 1000 | Extra long | 2000 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 85 | 3410023 |

REMA HPTR Stainless steel pallettruck



The semi stainless steel hand pallet truck is produced for the food industry and is satisfy hygiene demands. European origin.

Properties

- On the semi stainless steel hand pallet truck the frame, handle, axel, bolts and pins are in stainless, while the bars, front/rear rocker arm are in galvanized.
- The hand pallet trucks can resist the most chemicals, such as salt and cleansing agent.
- The semi stainless steel hand pallet truck have a simple and reliable hydraulic system with built-in automatic neutral position valve.
- Pump unit is zinc sprayed and painted afterwards.

Standard delivery

- Fork rollers and steering wheel of nylon.
- Tandem fork rollers.

Norm:

- EN 1526

| Type | S.W.L. (kg) | Dimensions (mm) | min height (mm) | width of fork (mm) | Material steering wheels | Material fork rollers | Weight (kg) | ProductId |
|---------------|----------------|-----------------|-----------------|-----------------------|-----------------------------|-----------------------|----------------|-----------|
| HPTR 449 TR/3 | 2500 | 1130 x 520 | 85 | 520 | Nylon | Nylon | 67 | 2804023 |

PTZ Heavy loads pallet truck

PTZ pallet trucks for extreme heavy loads

Properties:

- Especially designed pump for easy lifting of heavy loads.
- PTZ-5 has steel steering wheels & steel tandem fork rollers for excellent manoeuvrability.
- PTZ-3 has nylon steering wheels & nylon tandem fork wheels.
- To ensure transportability, pallet trucks are fitted with lifting eyes (PTZ-5).

Norm:

- EN12100-1/2, EN 3691-5



PTZ-50TSS



PTZ-30TNN

| Type | S.W.L. (kg) | Dimensions (mm) | min height (mm) | width of fork (mm) | Material steering wheels | Material fork rollers | Weight (kg) | ProductId |
|-----------|----------------|-----------------|-----------------|-----------------------|-----------------------------|-----------------------|----------------|-----------|
| PTZ-30TNN | 3000 | 1150 x 540 | 90 | 210 | Nylon | Nylon | 90 | 3410030 |
| PTZ-50TSS | 5000 | 1150 x 580 | 90 | 210 | Steel | Steel | 192 | 3401050 |

PTE Low pallet truck



PTE low pallet truck has a very low constructional height.

Properties 3410041:

- Low construction height 55 mm.
- Lifting height: 55 up to 165 mm.
- Dimension steering wheel: 180 x 50 rubber.
- Dimension fork roller 50 x 61 mm Polyurethane.

Properties 3410042:

- Extreme low construction height 36 mm.
- Lifting height: 36 up to 100 mm.
- Dimension steering wheel: 145 x 50 Polyurethane.
- Dimension fork roller 34 x 58 mm Polyurethane.

Norm:

- EN12100-1/2, EN 3691-5

| Type | S.W.L. (kg) | Fork length x width (mm) | lowest fork position (mm) | Width per fork (mm) | Material steering wheel | Material fork roller | Weight (kg) | ProductId |
|--------------|----------------|-----------------------------|------------------------------|------------------------|----------------------------|----------------------|----------------|-----------|
| PTE-200TPR | 2000 | 1150 x 540 | 55 | 160 | Rubber | Polyurethane | 72 | 3410041 |
| PTE-X 200TPS | 1000 | 1150 x 540 | 36 | 160 | Polyurethane | steel | 70 | 3410042 |

PTW wegende pallettruck

PTW weighing pallet trucks are supplied with a European digital read-out unit.



Properties

- Digital read-out unit.
- 4 measurement points in forks.
- Accuracy approximately ,1% (approx 2 kg at 2 kg).
- LED display with 18 mm high digits, scale division 1 kg.
- Power supply: 4 AA batteries.
- Duration of batteries is approx 1 year based on daily use
- Steering wheels : polyurethane.
- Temperature : -1 tot +4° C.
- Automatic power economy mode, to save battery
- Design according to IP 65 (Nema 4) /



Norm:

- EN12100-1/2, EN 3691-5

| Type | S.W.L. (kg) | Dimensions (mm) | Lowest fork position (mm) | Width per fork (mm) | Material steering wheel | Material fork roller | Weight (kg) | ProductId |
|-------|----------------|-----------------|------------------------------|------------------------|----------------------------|----------------------|----------------|-----------|
| PTW-N | 2000 | 1150 x 555 | 85 | 180 | Polyurethane | Polyurethane | 117 | 3401047 |

PTH-M Manual high lifter



Manoeuvrability of pallet trucks combined with the lifting height of scissor tables.

Properties

- As a results of the supports, high stability even at highest position.
- Diameter fork roller: 82 mm.

Norm:

- EN12100-1/2, EN 3691-5

| Type | S.W.L. (kg) | Dimensions (mm) | Dimensions L x W x H (mm) | width of fork (mm) | Lifting height (mm) | Lifting height per lever stroke (mm) | min height (mm) | Model fork roller | Diameter fork wheels (mm) | Weight (kg) | ProductId |
|-------|----------------|--------------------|---------------------------------|-----------------------|---------------------------|--|--------------------|----------------------|---------------------------------|----------------|-----------|
| PTH-M | 1000 | 1190 x 560 | 1600 x 560 x 1300 | 160 | 800 | 15 | 85 | single | 82 | 128 | 3401051 |

PTH-E electric high lifter



Manoeuvrability of pallet trucks combined with the lifting height of scissor tables.

Properties

- Manoeuvrability of pallet trucks combined with the lifting height of scissors tables.
- By means of supports, high stability even at highest position.
- Lifting height per movement: 15 mm.
- Steering wheels : polyurethane.
- Fork rollers : polyurethane - single. 82 mm.
- Lifting height : 85 to 800 mm.

Electric properties:

- Battery: 60 Ah/12Vdc.
- Included battery charger.
- Full charge about 60 x lifting.
- Can also lift manually.

Norm:

- EN12100-1/2, EN1175-1

| Type | S.W.L. (kg) | Dimensions (mm) | Dimensions L x W x H (mm) | width of fork (mm) | Lifting height (mm) | Lifting height per lever stroke (mm) | min height (mm) | Model fork roller | Diameter fork wheels (mm) | Weight (kg) | ProductId |
|-------|----------------|--------------------|---------------------------------|-----------------------|---------------------------|--|--------------------|----------------------|---------------------------------|----------------|-----------|
| PTH-E | 1000 | 1190 x 580 | 1600 x 580 x 1300 | 160 | 800 | 15 | 85 | single | 82 | 150 | 3401053 |

HC Skid lifter



HC-100

With the supplied plate table, these pallet trucks can be converted to lifting tables with one movement of the hand.

Properties

- Combination of pallet truck and lift table.
- Ideal for your loading and unloading operations.
- Continuous-welded heavy steel frame and forks handle heavy loads with ease.
- Easy-to-use control lever, plus two parking brakes on steering wheels.
- A steering handle on 1000 kg models for easier and comfortable turning.

Technical specifications

- lifting height max. 835 mm.
- Dimensions steering wheel 150 x 40 mm Polyurethane.
- Dimensions fork roller 72 x 68 mm Polyurethane.

Norm:

- EN12100-1/2, EN1570-1



HC-50

| Type | S.W.L. (kg) | Dimensions (mm) | Lifting height per lever stroke (mm) | min height (mm) | width of fork (mm) | Material steering wheels | Material fork rollers | Model fork roller | Weight (kg) | ProductId |
|--------|----------------|--------------------|---|--------------------|-----------------------|-----------------------------|--------------------------|----------------------|----------------|-----------|
| HC-50 | 500 | 1115 x 530 | 20 | 85 | 160 | Polyurethane | Polyurethane | single | 122 | 3469001 |
| HC-100 | 1000 | 1115 x 530 | 10 | 85 | 160 | Polyurethane | Polyurethane | single | 150 | 3469003 |