



Wireless remote control



L4-L6



L6B



TM-70/1-13



HYBRIDE

With a Rema radio remote system you are assured of a user-friendly, flexible and above all safe ergonomic remote control. Can be used with existing or new supply machines.

Properties

- Working range of 100 meters open area.
- LED display transmitter in operation.
- Functions hoisting / traveling / crane driving, 1 or 2 speeds.
- Transmitters are equipped with an emergency stop class 3.
- Adjustable frequencies (TM-70- 433/870/915 Mhz).
- Ambient temperature -20 ° C to + 65 ° C.

Standard delivery

- 1 hand transmitter with cord L-series.
- 1 receiver 24 VAC or 230 VAC.
- L-series including non-rechargeable batteries type AA.
- TM-70 including charger and battery.

Option

- Control multiple hoists with one hand transmitter (TM70).
- Crane driving.
- Other voltages on request.
- Assembly support plate.

Type	Function	Number of speed	Dimension of receiver L x B x D (mm)	Dimension of transmitter L x B x D (mm)	Protection class IP	Current (VAC)	Weight (kg)	ProductId
I-HYBRIDE	up/down/left/right	2	151 x 129 x 61	160 x 75 x 45	65	24	0,64	0725300
TM-70/1.13	up/down/left/right/crane drive	2	285 x 200 x 110	215 x 70 x 52	65	24	0,46	0725500
1-L4	up/down	1	161 x 74 x 52	163 x 49 x 45	65	24	0,155	0725700
1-L6	up/down/left/right	1	161 x 74 x 52	163 x 49 x 45	65	24	0,155	0725702
1-L6B	up/down/left/right	2	167 x 154 x 88	163 x 49 x 45	65	24	0,28	0725706