


Manille droite axe à boulonner goupillé type G-4153



Caractéristiques

- Corps et axe en acier haute résistance
- Galvanisé
- Grade 6
- Coefficient de sécurité: 6 : 1
- Température d'utilisation de -40°C jusqu'à +200°C
- Selon EN 13889



Type	CMU (kg)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	No.article
G4153-1/2	2000	13	16	22	43	0.37	3014009
G4153-5/8	3250	16	19	27	51	0.65	3014011
G4153-3/4	4750	19	22	31	59	1.06	3014013
G4153-7/8	6500	22	25	36	73	1.56	3014015
G4153-1	8500	25	28	43	85	2.32	3014017
G4153-1.1/8	9500	28	32	47	90	3.28	3014019
G4153-1.1/4	12000	32	35	51	94	4.51	3014021
G4153-1.3/8	13500	35	38	57	115	5.93	3014023
G4153-1.1/2	17000	38	42	60	127	7.89	3014025
G4153-1.3/4	25000	45	50	74	149	13.4	3014027
G4153-2	35000	50	57	83	171	16.86	3014029
G4153-2.1/4	42500	57	65	95	190	24.56	3014031
G4153-2.1/2	55000	65	70	105	203	32.65	3014033