


## RVS Ketting (NIET VOOR HIJSDOELEINDEN)




Volgens DIN-763, AISI-316

Type	Veilige werklust (kg)	B (mm)	D (mm)	P (mm)	Gewicht (kg/st/m)	Artikelnummer
4 x 32	100	16	4	32	0.28	2685509
5 x 35	160	20	5	35	0.28	2685511
8 x 52	400	32	8	52	1.13	2685515

## RVS Ovale karabijnhaak (NIET VOOR HIJSDOELEINDEN)



AISI-316




Type	Veilige werklust (kg)	D (mm)	B (mm)	P (mm)	S (mm)	Gewicht (kg/st/m)	Artikelnummer
OK-4MM	250	4	12	32	5.5	0.01	2685704
OK-5MM	375	5	13	39	6.5	0.02	2685705
OK-6MM	500	6	14	45	7.5	0.04	2685706
OK-8MM	1.000	8	18	58	9.5	0.08	2685708
OK-10MM	1.250	10	22	69	12.0	0.14	2685710

## RVS D-sluiting (NIET VOOR HIJSDOELEINDEN)



AISI-316




Type	Veilige werklust (kg)	A (mm)	B (mm)	D (mm)	L (mm)	Gewicht (kg/st/m)	Artikelnummer
D-4 D-sluiting	180	8	16	4	14.0	0.01	2685604
D-5 D-sluiting	220	10	20	5	14.5	0.02	2685605
D-6 D-sluiting	260	12	24	6	21.0	0.02	2685606
D-8 D-sluiting	420	16	32	8	28.0	0.06	2685608
D-10 D-sluiting	560	20	40	10	36.0	0.13	2685610
D-12 D-sluiting	1.040	24	48	12	44.0	0.20	2685612

## RVS Karabijnhaak (NIET VOOR HIJSDOELEINDEN)



AISI-316



Type	Veilige werklust (kg)	A (mm)	D (mm)	D1 (mm)	L (mm)	Gewicht (kg/st/m)	Artikelnummer
K-5MM	100	6	5	10	50	0.02	2685805
K-6MM	150	8	6	11	60	0.02	2685806
K-8MM	288	8	8	13	80	0.06	2685808
K-10MM	363	10	10	16	100	0.12	2685810