REMA Work made easy.
HOISTING & LIFTING



D-shackle with nut-bolt secured by split pin type G-4153

Product information

Galvanized steel with a high tensile strength suitable for temperatures between -20 ° C and + 200 ° C. Equipped with nut-bolt secured by split pin

Marking: According to standard, CE-marked
Standard: EN 13889

Safety factor: 6
Grade: 6

Part Code	GTIN No.	WLL ton	Model	A mm	B mm	C mm	D mm	Weight kg
3014009	8717365013751	2	G4153-1/2	13	16	22	43	0,37
3014011	8717365013768	3,25	G4153-5/8	16	19	27	51	0,65
3014013	8717365013775	4,75	G4153-3/4	19	22	31	59	1,06
3014015	8717365013782	6,5	G4153-7/8	22	25	36	73	1,56
3014017	8717365013799	8,5	G4153-1	25	28	43	85	2,32
3014019	8717365013805	9,5	G4153-1.1/8	28	32	47	90	3,28
3014021	8717365013812	12	G4153-1.1/4	32	35	51	94	4,51
3014023	8717365013829	13,5	G4153-1.3/8	35	38	57	115	5,93
3014025	8717365013836	17	G4153-1.1/2	38	42	60	127	7,89
3014027	8717365013843	25	G4153-1.3/4	45	50	74	149	13,4
3014029	8717365022999	35	G4153-2	50	57	83	171	16,86
3014031	8717365025792	42,5	G4153-2.1/4	57	65	95	190	24,56
3014033	8717365025808	55	G4153-2.1/2	65	70	105	203	32,65

Blueprint

