



DLB brake winch

Product information



Properties

- Zinc-plated housing (DL2500G has a ungalvanized drum).
- Fitted with automatic load pressure brakes.
- For extra safety, they are fitted with locking pawls.

Standard delivery

- Does not include cable.

Options

- Steel wire rope according DIN 3060 with safety hook.
- Sling belt according DIN 3060 with safety hook.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Part Code	GTIN No.	WLL ton	Model	Cable Diameter mm	Lift/crank turn (mm)	Gear ratio	Max. reel capacity mm	Force on the handle (kg)	Drum mm	Length handle mm	Weight kg
2117010	8717365110580	0,159	DLB-350A	3	22,5	3.2 :1	25	10	26 x 52	178	3
2117011	8717365008979	0,36	DLB-800AG	4	36	4.4 :1	23	12	48 x 53	178	3
2117013	8717365008986	0,545	DLB-1200AG	5	39	5.4 :1	19,7	19	64 x 51	238	4
2117015	8717365008993	0,68	DLB-1500AG	6	40	5.4:1	15,1	18	64 x 62	305	5
2117016	8717365009006	0,905	DLB-2000AG	7	30	17.3 :1	8,9	8	64 x 54	238	7
2117017	8717365009013	1,135	DLB-2500G	8	23	12.0 :1	7,4	13	79 x 66	244	12

